

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/026016 A1(51) International Patent Classification⁷: **H05K 13/04**

[JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).

(21) International Application Number:
PCT/JP2003/011602

(72) Inventors; and

(22) International Filing Date:
11 September 2003 (11.09.2003)(75) Inventors/Applicants (for US only): **OKUDA, Osamu** [JP/JP]; 35-1-C202, Wakamiya, Tamaho-cho, Nakakoma-gun, Yamanashi 409-3803 (JP). **KIDO, Kazuo** [JP/JP]; 4335-3, Osato-cho, Kofu-shi, Yamanashi 400-0053 (JP). **UCHIDA, Hideki** [JP/JP]; 2080-16, Saijo, Showa-cho, Nakakoma-gun, Yamanashi 409-3866 (JP).

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:
No. 2002-267950
13 September 2002 (13.09.2002) JP
No. 2002-268010
13 September 2002 (13.09.2002) JP
No. 2003-277293
22 July 2003 (22.07.2003) JP(74) Agents: **KAWAMIYA, Osamu** et al.; AOYAMA & PARTNERS, IMP Building, 3-7, Shiromi 1-chome, Chuo-ku, Osaka-shi, Osaka 540-0001 (JP).

(81) Designated States (national): CN, US.

(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(71) Applicant (for all designated States except US): **MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD.**Published:
— with international search report

[Continued on next page]

(54) Title: **COMPONENT PLACING HEAD AND ORIGIN DETECTION METHOD OF COMPONENT PLACING HEAD**(57) **Abstract:** A component placing head (100) provided with spline shafts (11), which are each elevatably supported by two spline nuts (12, 13), is provided with a cylindrical member (14, 15, 16) that is fixed to the outer peripheral portions of the spline nuts and joins the spline nuts to each other to put the same into an integrated state. Further, the cylindrical member is rotatably supported on a head frame (40) via two bearing sections, reducing the amount of the bearing sections to be provided. With this arrangement, high-accuracy component placement and downsizing of the component placing head can be achieved.



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.